


FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING







| - | 5.00±0.10 |
|---|-----------|
| | |
| | |
| | |

| REV. 001 | VALUE |
|----------------------------|---|
| CENTER WAVELENGTH (CWL) | 394 ± 2nm |
| FULL WIDTH HALF MAX (FWHM) | 10 ± 2nm |
| MINIMUM TRANSMISSION | ≥85% |
| BLOCKING | 200 - 1200nm |
| SURFACE QUALITY | 80-50 |
| CONSTRUCTION | MOUNTED IN BLACK ANODIZED ALUMINUM RING |
| COATING TYPE | HARD COATED |
| DURABILITY | MIL-C-48497A, SECT. 3.4.1 |
| ENVIRONMENTAL | MIL-STD-801F, SECT. 507.4 |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

| | | Edmund Optics® |
|-------------------|-------|---|
| RD ANGLE OJECTION | TITLE | OD4, Ø50mm, 394nm x 10nm, HC, BP FILTER |

THIRD ANGLE PROJECTION TITLE OD4, Ø50mm, 394nm x 10nm, HC, BP FILTER

ALL DIMS IN mm DWG NO 65192 SHEET 1 OF 1