



NOTES:

1. SUBSTRATE:  
N-BK7
2. COATING (APPLY ACROSS COATING APERTURE)  
S1: Aluminum with Protected Overcoat  
R(AVG)>85% FROM 400-700nm, @ 45° AOI

S2: NONE

 FINE GRIND SURFACE


4. RoHS COMPLIANT



**FOR INFORMATION ONLY:  
DO NOT MANUFACTURE  
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE  
DIMENSIONS ARE FOR REFERENCE ONLY

REV. A	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	40-20	40-20
CLEAR APERTURE	63.64 x 45.00	45.00 x 45.00
COATING APERTURE	63.64 x 45.00	45.00 x 45.00
SURFACE FLATNESS	$\lambda/8$	$\lambda/8$
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION 

ALL DIMS IN mm

 **Edmund Optics®**

TITLE	50mm, Aluminum Coated, N-BK7 High Tolerance RA Prism
DWG NO	65931
SHEET	1 OF 1