

NOTES:

- 1. SUBSTRATE:
 ZINC SELENIDE (ZnSe)
- 2. SURFACE S2 TO BE PARALLEL WITH S1 TO <1 arcmin
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: RAVG ≤5.0% @ 8 - 12µm



5. Rohs Compliant





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
SURFACE FLATNESS	λ/10 @ 10.6μm	λ/10 @ 10.6μm
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED
SURFACE QUALITY SURFACE FLATNESS	60-40 λ/10 @ 10.6μm	60-40 λ/10 @ 10.6μm

THIRD ANGLE PROJECTION		TITLE	
ALL DIMS IN	mm	DWG NO	

Ø12.5mm x 2mm THICKNESS, 8 - 12µm	
COATED, ZnSe WINDOW	

Edmund Optics®

DIMS IN mm DWG NO 68499 SHEET 1 OF 1