## NOTES:


1. SUBSTRATE MATERIAL: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: VIS-NIR (400-1000nm) R(ABS) ≤0.25% @ 880nm R(AVG) ≤1.25% @ 400 - 870nm R(AVG) ≤1.25% @ 890 - 1000nm

3. FINE GROUND SURFACE

4. RoHS COMPLIANT





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	EFL	18.00		<b>B</b> <sup>®</sup> Edmund Optics <sup>®</sup>
SHAPE	CONVEX	PLANO	BFL	16.81		
RADIUS	9.30	INFINITY	THIRD ANGLE PROJECTION		- TITLE	6mm DIA X 18mm FL VIS-NIR COATED, CYLINDER LENS
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø5.40	Ø5.40				
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	69767 SHEE 1 OF