## NOTES:


1. SUBSTRATE MATERIAL: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: VIS-NIR (400-1000nm) R(ABS) ≤0.25% @ 880nm R(AVG) ≤1.25% @ 400 - 870nm R(AVG) ≤1.25% @ 890 - 1000nm

3. FINE GROUND SURFACE

4. Rohs Compliant





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	EFL	75.00		Edmund Ontice
SHAPE	CONVEX	PLANO	BFL	73.68		Edmund Optics®
RADIUS	38.76	INFINITY	THIRD ANGLE PROJECTION		TITLE	12.5mm DIA X 75mm FL VIS-NIR COATED, CYLINDER LENS
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø11.50	Ø11.50		ı		
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	69771 SHEET 1 OF 1