
NOTES:


- SUBSTRATE: UV GRADE FUSED SILICA 1.
- 2. COATING (APPLY ACROSS COATING APERTURE) \$1 & \$2: RAB\$ ≤0.25% @ 880nm RAVG ≤1.25% @ 400 - 870nm RAVG ≤1.25% @ 890 - 1000nm
- 3. SURFACE S2 TO BE PARALLEL TO SURFACE S1 WITHIN <5 ARCSEC

∕4.∖

FINE GRIND SURFACE

5. **ROHS COMPLIANT**





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

1 OF 1

	\$1	\$2	
SHAPE	PLANO	PLANO	
SURFACE QUALITY	20-10	20-10	
CLEAR APERTURE	Ø60.00	Ø60.00	
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	

				Edmund Optics®		
	THIRD ANGLE PROJECTION	\$	TITLE	75mm DIA., 5mm THICK, VIS-NIR COATE FUSED SILICA WINDOW	D λ/10	
_	ALL DIMS IN	mm	DWG NO	34044	SHEET	

36966