

NOTES:

- 1. SUBSTRATE: FUSED SILICA
- 2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN 15±1 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)
 - \$1: R(ABS) ≤ 0.25% @ 633nm \$2: NONE
- 4. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 5. ROHS COMPLIANT





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHAPE	\$1 PLANO	S2 PLANO	-	B	Edmund Optics®
SURFACE FLATNESS	λ /20	λ /20			TRANSMISSION FLAT 1/20 WAVE 4"
SURFACE QUALITY	20-10	20-10	THIRD ANGLE PROJECTION	TITLE	TRANSIVIISSION LEAT 1/20 VVAVE 4
CLEAR APERTURE	100.0	100.0			CUETT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	37115 SHEET 1 OF 1