

## NOTES:

MATERIAL:

BOROSILICATE GLASS CONTAINING ELONGATED SILVER CRYSTALS

- 2. COATING SPECIFICATION: S1 & S2: BBAR COATING R(AVG) < 0.25% @ 1510 - 1590nm @ 0° AOI
- 3. EXTINCTION RATIO: >100,000:1
- 4. RoHS: COMPLIANT





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

PARIS IU INI	5 DRAWING			<b>Edmund Optics</b> ®
	<b>S</b> 1	\$2		25mm Dig. 1550nm. Corning PolgroorTM Class

	\$1	S2		1		25mm Dia 1550nm Ca	ornina Polarcor <sup>TM</sup> Glass
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION		TITLE	25mm Dia., 1550nm, Corning Polarcor™ Glass Polarizer	
SURFACE QUALITY	40-20	40-20					
BEVEL MAX FACE	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	13621	SHEET 1 OF 1