NOTES:

- SUBSTRATE: FUSED SILICA
- 2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN < 3 ARCMIN
- 3. COATING PERFORMANCES ACROSS CLEAR APERTURE:

T(ABS) > 99.8% @ 1064nm @ 0° AOI




4. FINE GRIND SURFACE




SURFACES ARE EXTREMELY FRAGILE, ANY CONTACT TO OPTICAL SURFACE WILL AFFECT PERFORMANCE. DO NOT TOUCH SURFACES AND DO NOT WIPE CLEAN.



6. UNTREATED ANNULUS 1.25mm FROM EDGE





PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2			
SHAPE	PLANO	PLANO			
SURFACE QUALITY	10-5	10-5			
CLEAR APERTURE	Ø20.32	Ø20.32			
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED			

	80	* Edmund Optics*
HIRD ANGLE	TITLE	25.4mm Dia., 6.35mm THICK, 1064nm

THIRD ANGLE PROJECTION	$\bigoplus \Box$	TITLE	NEBULAR™ LASER LINE WINDOW	m
ALL DIMS IN	mm	DWG NO	14650	SHEET 1 OF 1