NOTES:

1. SUBSTRATE: ALUMINUM

2. COATING (APPLY ACROSS COATING APERTURE) \$1: R(ABS) > 99% @ 480 - 580nm

S2: NONE


3. FINE GRIND SURFACE


4. OFF-AXIS ANGLE(°): 30

5. REFLECTED WAVEFRONT ERROR, P-V: $< \lambda/10$

6. SURFACE ROUGHNESS: < 4nm RMS

7. RoHS: COMPLIANT





PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	AXICON	PLANO
SURFACE QUALITY	40 - 20	N/A
CLEAR APERTURE	Ø22.86	N/A
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION	$\phi \lhd$	TITLE
ALL DIMS IN	mm	DWG NO

	Edmund Optics®
TITLE	3° AXICON ANGLE, 480 - 580°, OFF-AXIS

SHEET

1 OF 1

TITLE	REFLECTIVE AXICON
	1 3° AXICON ANGLE, 480 - 580°, OFF-AXIS

14564